

SW 500-TOUCH SCREEN

(5T 06/T) TERAPIE UNDE SCURTE



CARACTERISTICI

- Iesiri continue si pulsate cu reglaj automat
- Putere in mod continuu: 400W
- Varf de putere max. in mod pulsat: 1000W
- Panou frontal cu display usor de citit
- Brate ajustabile pt. usoara aplicarea a electrozului

ACCESORII STANDARD

- N.1 Suport tip brat pt. electrozi (H1002201)
- N.2 Cabluri unde scurte (C/M)
- N.2 Electrozi tip disc 150 mm (T1E2)
- N.1 Cablu alimentare (C/AI)
- N.1 Cheie hexagonal (CES)

ACCESORII OPTIONALE

- Electrod tip disc 80 mm (T1E1)
- Electrod cauciuc flexibil 100x160 mm (T1PI1)
- Electrod cauciuc flexibil 140x220 mm (T1PI2)
- Suport textil pt. electrod T1PI1 (F11)
- Suport textile pt. electrod TiPI1 (F12)
- Suport bumbac pt. electrod T1PI1 (TS1)
- Suport bumbac pt. electrod T1PI2 (TS2)
- Banda elastic 100 cm (F7)
- Diplod (DPL)
- Suport tip brat pt. Diplod (H1002101)
- Monod (MNO)

MODURI DE OPERARE

Generator frecventa: 27,12 MHz

Mod iesire: reglaj automat in mod continuu si pulsat

Putere iesire: ajustabila in limita 0-400 W in mod continuu si 0-1000W in mod pulsat

Durata pulsului: 400 μ s

Frecventa: ajustabila in limita 20-200 Hz in pasi de 10

Timer: ajustabil in limita 1-30 min.

Alimentare: 230V sau 110 V; 50/60 Hz

Putere intrare: 2000 VA

Clasa siguranta: tip I BF

